

Products and Services

Product Overview

OPERA

- > Voice Quality Testing
- > Audio Quality Testing
- > OPERA™ Distributed Network Test System
- > OPERA™ Control Center Software
- > Technical Specifications
- > Why OPERA sets the Standards
- > Applications
- > Configurations and Ordering Information
- > Download Datasheet
- > OPERA™ Demoversion

Services

Strategic Partnerships

Standards

Whitepapers

Literature

News + Events

Our Customers

International Sales

Contact Information

Contact Form

OPERA™
Voice/Audio
Quality Analyzer -
 The Objective
 Perceptual Signal
 Quality Analyzer
 setting the Standards.



PRODUCT
OVERVIEW

The OPERA™ Voice/Audio Quality Analyzer represents the latest developments to objectively evaluate and assure the quality of compressed voice and wide-band audio signals, based on modeling the human ear. With OPERA you can achieve a comprehensive analysis of the end-to-end quality of today's and next generation networks, such as VoIP, VoDSL, VoATM, ISDN, GSM, POTS, from the caller to the callee. Also, you can test the audio quality of compression formats such as MP3, AAC, AC3, Microsoft Windows Media, from the studio source to the receiver, or from the server to the client.

> Comprehensive Scalability

For the test engineer, one of the issues is how to apply a computer model of the human ear to a test circuit, or to a live network environment. For this reason, OPTICOM developed OPERA as an open, easy to configure hardware platform that can process perceptual models, which are implemented just by software. The basis of the OPERA system is a portable 'lunch box' type of PC host system. Four slots can take various kinds of interfaces. Alternatively, OPERA is now also available in a rack-mountable form factor. For R&D and lab applications, a cost effective software-only version with reduced functionality is offered, as well.

> OPERA Form Factors:

- **OPERA™ Portable Analyzer** ('Lunch-box') stand-alone;
- **OPERA™ 19" Server**, stand-alone and server
- **OPERA™ Distributed Network Test System**, incl. 19" Server, and/or Portables, automated QoS surveillance,
- **OPERA™ Software Suite** (file-based analysis, only)

> Key Functionality, Voice Quality Testing

- **PESQ**, perceptual evaluation of speech quality according to ITU-T rec. P.862 [2001]. Combines PSQM with PAMS, optimized for VoIP and hybrid end-to-end applications
- **PSQM**, perceptual speech quality measure according to ITU-T rec. P.861 [1996]
- **PSQM+**, advanced perceptual speech quality measure according to ITU-T COM 12-20 [1998]
- **PSQM/IP**, perceptual speech quality measure according to ITU-T rec. P.861 [1996], incl. advanced delay compensation for end-to-end measurements,

> Key Functionality, Audio Quality Testing

> Common Functionality

> Interfaces for Telecom Applications

> Interfaces for Audio Applications

> Download more detailed Technical Specifications

developed by OPTICOM

- **Echo measurement** based on real speech, Echo Return Loss ERLmom, ERLpeak, ERL vs. delay
- **PEAQ**, perceptual evaluation of audio quality according to ITU-R rec. BS.1387 [1999], Basic and Advanced Model
- **Most flexibly configurable unified hardware test platform for perceptual voice and audio quality measurements on the market**
- **On-line real-time acquisition and analysis capability for voice and audio quality testing (hardware only)**
- **Advanced delay compensation for end-to-end measurements, suitable for constant and variable delays (VoIP)**
- **User friendly graphical Windows interface for interactive operation, extensive graphical diagrams and output representations available,**
- **Comprehensive scripting functionality**
- **User friendly graphical 'control center' user interface for automated use and surveillance of QoS**
- **Four port analog POTS** interface (standard);
- **Dual port E1/T1 Trunk** interface option; software configurable, 120 Ohm RJ48C;
- **Quad port E1/T1 Trunk** interface option; software configurable, 120 Ohm RJ48C; (available on request)
- **2x 24 bit analog/digital audio I/O** interface option for multimedia terminal testing (e.g. PC-to-phone)
- **OPERA™ multimedia adapter set**, (e.g. for PC-to-phone, multimedia terminal testing)
 - incl. stereo XLR(m)-to-jack(3,5mm), stereo XLR(f)-to-jack(3,5mm)
 - incl. 2x XLR(m)-to-Cinch, 2x XLR(f)-to-Cinch
- **OPERA™ fixed and mobile phone adapter box** [Note: 2x 24 bit analog/digital audio I/O required]
- **2x Stereo 24 bit analog/digital audio I/O** interface (standard), sym. XLR, AES/EBU
- **OPERA™ multimedia adapter set**, (e.g. for PC-to-phone, multimedia terminal testing)
 - incl. stereo XLR(m)-to-jack(3,5mm), stereo XLR(f)-to-jack(3,5mm)
 - incl. 2x XLR(m)-to-Cinch, 2x XLR(f)-to-Cinch
- > Download **OPERA™ Analyzer – Technical Specifications** [[as PDF / 50 kb](#)]
- > Download **OPERA™ Control Center – Technical Specifications** [[as PDF / 750 kb](#)]
- > Download **OPERA™ Software Suite – Technical Specifications** [[as PDF/ 40 kb](#)]
- > Download **OPERA data sheet** [[as PDF/ 823 kb](#)]
- > Download **printable version of this page** [[as PDF/ kt](#)]

[top]